

## PRODUCT DATA SHEET

---

Part number 219504

---

EAN 4015609013289

Manufacturer WALTHER-WERKE

WEEE-Reg.-Nr: DE 22131895

### Product description

---

Waterproof Plug 16A 5P 4h with external cable gland



Product Image

### Detailed product description

---

WALTHER Plug 16A 5P 110V 4h IP67

made from PA6 material

with screw terminal

and external cable gland

Increased safety due to injected 2K seal and two contact screws.

### Ordering information

---





order unit	Piece
customs number	85366990
net weight	0.236 kg
packing quantity (VPE)	10
length of the packaging	0.31 m
width of the packaging	0.195 m
depth of the packaging	0.14 m
gross weight(VPE)	2.508 kg

### Conformities

---

CE conformity	√
RoHS directive	2011/65/EU
RoHS directive	2015/863/EU
REACH regulation	1907/2006

## Certification

VDE/ENEC certification	40024787	
UL certification	No. E329476	
UL certification	No. E188992	
EAC certification	BY112.02.01.020 06090	


## Classification system

classification system	ETIM_7.0
ETIM Class	EC000140

## Technical product data

IEC-amperage	16 A
Amperage according to UL/CSA (for UL-version)	20 A
Number of poles	5
Voltage according to EN 60309-2	110 V (50+60 Hz) yellow
Clock hour position	4 h
Identification colour	Yellow
Conductor cross-section	1 - 2.5 mm <sup>2</sup>
Cable diameter	7.5 - 18.5 mm
Cable strip length	35 mm +/- 2.5 mm
Cable ferrules length	10 mm +/- 1 mm
Maximum torque terminal screw	0.8 Nm
Maximum torque cable gland	4 Nm
Degree of protection (IP)	IP67
Connection system	Screwed terminal
Contact material	Nickel-plated brass
Cable entry	Swivel
Angle of plug	Straight
Material	Plastic
Inflammability class of insulation material according to with UL94	V2

## Dimension sheet



<b>Amp.</b>	<b>16</b>	<b>16</b>	<b>32</b>	<b>32</b>
<b>Pole</b>	<b>4</b>	<b>5</b>	<b>3 / 4</b>	<b>5</b>
<b>d</b>	150-161	150-161	174-183	174-183
<b>Ø e</b>	Ø 65	Ø 65	Ø 72	Ø 72
<b>m</b>	111	111	127	127
<b>n</b>	36,5	36,5	45,5	45,5
<b>Ø u</b>	Ø 81	Ø 89	Ø 95	Ø 100
<b>Ø p</b>	7,5-18,5	7,5-18,5	10-22,5	10-22,5