

## PRODUCT DATA SHEET

---

|                   |               |
|-------------------|---------------|
| Part number       | 436RW         |
| EAN               | 4015609183500 |
| Manufacturer      | WALTHER-WERKE |
| WEEE-Reg.-Number: | DE 22131895   |

### Product description

---

MONDO wall socket 32A 5P 6h built-in with flush-mounted socket and plaster-compensating flange in pure white



Product Image

### Detailed product description

---

WALTHER Wall socket 32A 5P 400V 6h IP44  
 from the MONDO series  
 made from PA6 material  
 in pure white (RAL 9010)  
 with flush-mounted socket and plaster-compensating flange  
 outer dimensions 90x90mm  
 The flat cover allows a low housing height  
 and is therefore suitable for prestigious areas.



### Ordering Information

---

|                         |          |
|-------------------------|----------|
| Order unit              | Piece    |
| Customs number          | 85366990 |
| Net weight              | 0,369 kg |
| Packing quantity (VPE)  | 5        |
| Length of the packaging | 0,31 m   |
| Width of the packaging  | 0,195 m  |
| Depth of the packaging  | 0,14 m   |
| Gross weight(VPE)       | 1,993 kg |

### Certificates

---

|                   |                       |                                                                                     |
|-------------------|-----------------------|-------------------------------------------------------------------------------------|
| VDE certification | 123021                |  |
| EAC certification | BY112.02.01.020 06089 |  |

## Classification system

|                       |          |
|-----------------------|----------|
| Classification system | ETIM_6.0 |
| ETIM Class            | EC001318 |

## Technical product data

|                         |                                  |
|-------------------------|----------------------------------|
| Current supply          | CEE 32 A                         |
| Number of poles         | 5                                |
| Voltage acc. EN 60309-2 | 400 V (50+60 Hz) red             |
| Clock hour position     | 6 h                              |
| Identification colour   | Red                              |
| Construction type       | Flush mounted socket with UP box |
| Configuration           | Closed cover                     |
| Colour                  | White                            |
| RAL-number              | 9010                             |

## Dimension sheet

